

CGP Europe
HYTAC Syntactic Plug Standard Sizing

		HYTAC-W, WF, WFT, FLX, FLXT, C1R														
		Standard Stock Sizes										Made to order				
Standard Rod Diameter:	inches	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	7.0	8.0	9.0	9.5	10.0	12.0
	mm	51	64	76	89	102	114	127	140	152	178	203	228	241	254	305
12" (305mm) Length												•	•	•	•	•
24" (610mm) Length		•	•	•	•	•	•	•	•	•	•					
Standard Block:		6.0" (152mm) T x 12.0" (305mm) W x 24.0" (610mm) L														
Standard Sheet Thickness:	inches	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0					
	mm	25	38	51	64	76	89	102	114	127	152					
24" (610 mm) W x 26" (660mm) L		•	•	•	•	•	•	•	•	•	•					
24" (610 mm) W x 60" (1524mm) L		•	•	•	•	•	•	•	•	•	•	60" /1524mm are made to order				

		HYTAC-B1X												
		Standard Stock Sizes												
Standard Rod Diameter:	inches	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	7.0	8.0	9.0		
	mm	64	76	89	102	114	127	140	152	178	203	229		
12" (305mm) Length														
24" (610mm) Length		•	•	•	•	•	•	•	•	•	•	•		
48" (1219mm) Length		•	•	•	•	•	•	•					On Request	
Standard Sheet Thickness:	inches	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0			
	mm	25	38	51	64	76	89	102	114	127	152			
24" (610mm) W x 24" (610mm) L		•	•	•	•	•	•	•	•	•	•			
24" (610mm) W x 48" (1219mm) L		•	•	•	•	•	•	•	•	•	•	On Request		



Custom Cut Sizing Available - Contact CGP Europe with requirements

CGP Europe 1 rue des épinettes, F-77400 Torcy France

Phone: +33 16005 6363

Fax: +33 1 6017 3653

Web: <http://hytac.free.fr>

E-mail: cgpeurope@free.fr

NOTE: All dimensions listed are nominal dimensions.

HYTAC-W, WF, WFT, FLX, FLXT and C1R standard stock tolerances are + 0%, - 1.5% of thickness or diameter

HYTAC-B1X tolerances are + .187" (5mm), - 0.0" (0mm) of thickness or diameter

CUSTOM CUT tolerances are +.125" (3mm), - 0.0" (0mm)

CUSTOM CAST tolerances are specified based upon tooling design